



POWERFUL VERSATILITY

The TurfCat® delivers superior versatility in a large area rotary mower that is simple to maintain. With nine deck configurations and five purpose-built attachments with quick-connect fittings, you can move from task to task with ease. The TurfCat solves a variety of needs with its ability to mow thick grass, produce the fine-cut striping required for sports fields, remove debris and snow, and destroy unsightly aerification cores. Spend more time on your to-do list with the TurfCat's all-hydraulic traction drive, cutting deck, and individual deck motors.

**9 DECK
CONFIGURATIONS**

**2WD
OR
4WD**

**25 HP
DIESEL ENGINE**

**60", 63", 72"
WIDTH OF CUT**



JACOBSEN® ADVANTAGE

For over 95 years, Jacobsen has been designing and manufacturing industry-leading turf maintenance equipment. A strong focus on engineering innovative technology has led to advancements that deliver impeccable quality of cut on user-friendly equipment.

EQUIPPED AS STANDARD

- Foldable ROPS
- Tilt-up seat and seatbelt

OPTIONS

- Carefree caster tires (for side discharge decks)
- Leaf mulcher kit for all rotary decks
- Canopy
- Additional counterweight
- Cab
- Class I Hitch
- Premium Suspension Seat

ENGINE	
TYPE	Kubota® D1105 E4B 4-cycle, 3-cylinder, liquid-cooled
HORSEPOWER*	24.8 hp (18.5 kw)
DISPLACEMENT	68.53 cu. in. (1.123 L)
AIR CLEANER SYSTEM	Dry type with dust evacuator
COOLING SYSTEM	Pressurized, sealed cooling system; coolant capacity: 6.8 qt. (6.4 L)
LUBRICATION	Fully Pressurized
OIL FILTER	Full-flow, replacement spin-on type
ELECTRICAL SYSTEM	40 amp alternator with 12V 410 CCA battery, fuse protected
FUEL CAPACITY	9 gal. (34 L)
TRACTION & DRIVE	
TRACTION DRIVE	Variable displacement hydraulic pump directly mounted to engine; individual hydraulic wheel motors
DECK DRIVE	Hydraulic PTO with hydraulic gear pump and motor with electro-hydraulic control valve
HYDRAULIC SYSTEM	6.8 gal (25.7 L) capacity
HYDRAULIC COOLING	Full-flow filter with oil cooler
SPEED (MAXIMUM)	
MOWING	0-10 mph (0-16 km/h)
TRANSPORT	0-10 mph (0-16 km/h)
REVERSE	0-4 mph (0-6.4 kph)
TIRES, BRAKES & STEERING	
TIRES	Front: 23 x 10.5, 4-ply, turf tread Rear: 20x10, 4-ply,turf tread
PARKING BRAKE	Foot pedal actuated parking brake
SERVICE BRAKES	Hydrostatic
STEERING	Hydrostatic with rear wheel steering
CUTTING UNITS	
CONSTRUCTION	Welded 11-gauge high-strength steel
CASTER WHEELS	Two 11 x 4.5 pneumatic, tubeless, 4-ply -side discharge decks Two 9 x 3.5 semi-pneumatic - rear discharge decks
CUTTING UNIT LIFT	Switch operated, electro hydraulic lift system
WEIGHT TRANSFER	Hydraulic weight transfer adjustable under seat
MOTOR / SPINDLE	Fixed displacement hydraulic spindle motor with 1 in. diameter shaft, self lubricated bearings.
CUTTING CAPACITY	60 in.= up to 3.3 acres (1.3 ha) per hour at 5.5 mph (9 km/h) 63 in.= up to 3.5 acres (1.4 ha) per hour at 5.5 mph (9 km/h) 72 in.= up to 4 acres (1.6 ha) per hour at 5.5 mph (9 km/h)
OVERALL CUTTING WIDTH	60 in. (1.52 m), 63 in. (1.60 m) or 72 in. (1.82 m)
WEIGHT & DIMENSIONS	
WEIGHT	2WD: 1,640 lbs. (744 kg) 4WD: 1,720 lbs. (780 kg)
LENGTH (with deck)	88 in. (2.2 m)
HEIGHT	ROPS up 83 in (2.12 m) ; Cab installed 84 in. (2.13 m) ; ROPS folded 57 in. (1.45 m)
WHEELBASE	53 in. (1.35 m)
WIDTH (without deck)	52 in. (1.32 m)

* Engine power is provided by engine manufacturer. Actual operating power output may vary due to conditions of specific use.

** Height-of-cut depends on turf condition, reel wear and bedknife installed.

NOTE: Specifications, while correct at time of printing, may change without notice.